

CARMEL GROUP INC.

MATERIAL SAFETY DATA SHEET

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

| | | |
|---|--|--|
| Product Modelling Wax Various Colors (Blue, Green & Red) | | Revision date 17-September-09 |
| Previous revision date 13-July-2007 | Product code IW42104, IW42109 & IW42110 | Material use Dental Wax |
| Manufacture's Name and issuing location CARMEL GROUP INC. 10220 ARMAND LAVERGNE AVE. MONTRÉAL, QUE. H1H 3N4 PHONE : 514-270-5377 FAX : 514-270-2025 INTERNET : www.carmelindustries.com | | EMERGENCY PHONE NUMBER CANUTEC 613-996-6666 |

SECTION 2 – CONPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Ingredients | CAS# | Amount | Exposure Limits | |
|---|------|--------|-----------------|-------|
| | | | LD/50 | LC/50 |
| None as defined by OSHA 29 CRF 1910.1200 | | | | |

SECTION 3 – HAZARD IDENTIFICATION

Emergency Overview

The product is not expected to present any unusual hazards in proper use (room temperature up to 104F/40C). Overheating is considered abnormal usage of the product.

| | |
|--------------|---|
| SKIN CONTACT | No danger at room temperature. |
| EYE CONTACT | Not likely to occur because solid sheets at room temperature. |
| INHALATION | No fume or aerosol at room temperature. |
| INGESTION | This material is essentially inert and non-toxic. Regardless it should not be ingested. |

Potential Health Effects (NFPA Classification)

| | | | |
|-----------------|-------------------|----------------|-------------------------------------|
| Fire hazard : 1 | Health Hazard : 0 | Reactivity : 0 | Personal Protection : See Section 8 |
|-----------------|-------------------|----------------|-------------------------------------|

0 = Minimal 1 = Slight hazard 2= Moderate Hazard 3 = Serious Hazard 4 = Severe Hazard

SECTION 4 – FIRST AID MEASURES

| | |
|-----------------|--|
| EYE CONTACT | Exposure to fumes, vapours or smoke of the thermally degraded product can result in irritation to the eye and direct contact of the molten material will cause eye injury and burns. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Call a physician to attend to the injury. |
| SKIN CONTACT | Exposure to fumes, vapours or smoke of thermally degraded product can result in irritation to skin and direct contact of the molten material will cause injury and burns. For burns apply running water over the injured area for 15 minutes. Do not attempt to remove any material bonded to skin. Call a physician to attend to the injury. |
| INHALATION | Remove individual to a well ventilated area for fresh air and call a physician to attend to the injury. |
| INGESTION | Material is not acutely toxic by ingestion. If material is ingested, do not induce vomiting. Call a physician. |
| ADDITIONAL INFO | |

SECTION 5 – FIRE FIGHTING MEASURES

| | |
|----------------------|---|
| Extinguishing | Treat as an oil fire. For small fire use CO ₂ , dry powder or foam. For large fire use |
|----------------------|---|

| | | | |
|--|---|---|----------------------------------|
| Media | alcohol-type foam, universal-type foam or water fog. | | |
| Special Fire fighting Procedure | Use water spray cool fire-exposed containers and structures. Do not direct a solid stream of water or foam into burning molten material; this may cause spattering and spread the fire. | | |
| Unusual Fire and Explosion Hazards | This product will burn if involved in a fire. This product will float upon water, so water spray is not suitable extinguishing agents as it may cause fire to spread. | | |
| SECTION 6 – ACCIDENTAL RELEASE MEASURES | | | |
| Small Spills | Not likely to occur in solid state. | | |
| Large Spills | Not likely to occur in solid state. | | |
| SECTION 7 – HANDLING AND STORAGE | | | |
| Handling procedures | None special needed. | | |
| Storage precautions | Normal precaution should be followed in handling and storage. Store in a dry place. Keep out of direct sunlight. Do not store at temperature : > 104F/40C | | |
| SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION | | | |
| PERSONAL PROTECTION (ONLY IF MOLTEN) | | | |
| Respiratory protection | No special respiratory protection is normally required. | | |
| Protective gloves | None are normally required. | | |
| Eye protection | No special eye protection is normally required. | | |
| Clothing | No special clothing recommended. | | |
| SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES | | | |
| Appearance Various Color Wax in Thin | Odour None | Physical state Solid @ 25°C / 77°F | Boiling point N / AV. |
| Melting point ~80°C/175°F | Specific gravity (H ₂ O=1) < 1 | Vapour pressure (mm Hg) < 0.01 @ 25°C / 77°F | Solubility in water Insoluble |
| Solubility in organic solvent Soluble | Partitioning coefficient N / AV. | Flash point N / AV. | Percent volatiles Nil |
| SECTION 10 – STABILITY AND REACTIVITY DATA | | | |
| Stability Stable | Hazardous polymerization Will not occur. | | |
| Incompatibility Normally unreactive; however avoid contact with strong oxidizing agent (ex. Peroxides, chlorine), Sunlight or ultraviolet light, heat or high temperature. | | | |
| Hazardous decomposition products Burning can produce noxious and toxic fumes, and the following combustion products : Oxides of carbon. | | | |
| SECTION 11 – TOXICOLOGICAL INFORMATION | | | |
| Carcinogenicity Not listed, not carcinogenic to date. | Mutagenicity / Teratogenicity Not listed | | |
| Irritancy of Material N / Av. | Sensitizing Capability N / Av. | | |
| Reproductive Effects None known | Synergistic Materials None known | | |
| SECTION 12 – ECOLOGICAL INFORMATION | | | |
| This product is stable in water, and can be mechanically separated from water. The water may be suitable for disposal in a biological waste water treatment plant. Not expected to be acutely toxic to aquatic organism. | | | |
| SECTION 13 – DISPOSAL CONSIDERATION | | | |
| Incineration is probably the best mean of disposal. Dispose of in accordance with appropriate Federal, State and local regulation. | | | |
| SECTION 14 – TRANSPORT INFORMATION | | | |

| | |
|--|---|
| Dot Classification Not regulated if shipped at temperature under 100C / 212F or in containers less than 450 liter. | |
| IMDG Classification Not regulated if shipped at temperature under 100C / 212F or in containers less than 450 liter. | |
| UN / NA Hazard No. Not Applicable. | |
| ICAO Classification Not regulated if shipped at temperature under 100C / 212F. | |
| Other Forbidden by air at temperature over 100C / 212F. | |
| SECTION 15 – REGULATORY INFORMATION | |
| SARA Status | Section 311, 312 and 313 : None |
| TSCA Status | Ingredients listed in the TSCA inventory. |
| OSHA Status | None |
| WHMIS Status | Not a controlled material |
| CPR Compliance | Not Known |
| SECTION 16 – OTHER INFORMATION | |
| N/AV=NOT AVAILBLE | |
| MSDS Originally made by Karl Pinard | Revised by Samia Ghezlaoui |

The information contained in this document is derived from data supplied to Carmel Industries by the manufacturers or distributors of the raw materials combined to form this product. To the best of our knowledge all hazards have been noted for the intended use of the product and, since Carmel Industries cannot control conditions of use, the end user is obliged to determine the conditions permitting safe use of the product.

CARMEL GROUP INC.
MODELLING WAX PRODUCTS

| Product code | Product Description |
|---------------------|---------------------------------|
| IW42104 | Blue Modelling Wax in 2 Oz Tin |
| IW42109 | Red Modelling Wax in 2 Oz Tin |
| IW42110 | Green Modelling Wax in 2 Oz Tin |